











Torque Tester – CapStar





Digital Bottle Cap Tester

The new CapStar cap closure torque tester is a simple and easy-tooperate digital torque tester, specifically designed for applications within the pharmaceutical, food & beverage industries, and many more.

By measuring torque, the CapStar can ensure the correct level of tension is in place on a wide range of caps and closures such as on medicinal or cosmetics containers, drinks bottles or food jars etc. With the CapStar's clear display and easy-to-view torque results, operators are able to guarantee production quality whilst ensuring contents – which could be potentially harmful – remain sealed and secured.

The CapStar helps to ensure the safety of products, prevent leaks and reduce the ergonomic issues associated with these products without compromising on safety, quality or freshness.

For optimal power management, the CapStar automatically switches to the highest voltage power source to save on battery life, yet still giving the option to pick it up and unplug to seamlessly run on battery power.

The CapStar is supplied with an adjustable component fixture for measuring bottles and containers, and is available in 2Nm, 4Nm and 6Nm ranges.

- ► Accurate digital measurement of bottle cap/closure release torque (sigma, mean and range).
- ► Accuracy ± 0.25% FSD.
- Automatic detection of the direction of rotation (right/left).
- ► Strong, durable and robust perfect for production, quality and testing environments.
- ► Built-in transducer and adjustable clamp fixture available in 2Nm, 4Nm and 6Nm sizes.
- ▶ Memory for 999 date- and time-stamped readings for complete traceability.
- Easy download of all measurement readings to a PC via Micro-USB port.
- ► Energy-saving and clear to read **OLED** display.
- ▶ 3-colour LED indication of torque measurement status.
- Drip-proof (IP45).
- ► Automatically switches to highest voltage power source (mains/ USB/batteries).

INFO Delivery incl. object clamping device, 2 Alkaline batteries Type C (,Baby'), operating instructions (English) and traceable factory calibration certificate (UKAS).

CapStar Model Item Code Part No. Torque Range Weight ozf·in lbf∙in cN⋅m N·m 0.2 - 2 2 Nm CapStar RSCS2-0002-CRXXXX C718361 28 - 283 1.8 - 18 20 - 200 3.0 40 - 400 0.4 - 4 3.0 4 Nm CapStar RSCS2-0004-CRXXXX C718351 57 - 566 3.5 - 356 Nm CapStar RSCS2-0006-CRXXXX C718371 85 - 849 5.3 - 53 60 - 600 0.6 - 6 3.0

Optional Components			
Model	Item Code	Part No.	Description
Long Pegs	BT-479-1-0	C718314	Long pegs for clamping large objects
PSU 5 VDC	RSXXA-0000-CRPXXX	C718XXX	Mains adaptor (no charging) 5 VDC



Recommendation: A torque tester should be chosen so that it is mainly used in its medium range. If you regularly have to work close to the max. load capacity, a larger model would be more advisable.



