

Digital Torque and Angle Wrench – DTC



SR's Latest Innovation

The 1250 Exacta Series transducer and all the functionality (except the radio capability) has been placed in the micrometer adjustable body. The result is a tool like no other. Agile. Slim. Lightweight.

In line with SR's systems approach to error proofing, you cannot set the wrench to a torque value beyond the wrench capacity. This is just one of the many features that are built into the DTC.

The DTC has a b/w display and colored light bands on the side of the wrench. Those bands change yellow to green when the target values are achieved. An auditory beep and the handle vibrates provide two additional modes of operator focused error proofing guidance.

The DTC results log is large enough for even the busiest assemblies. Using the mini-USB port, and DTC Connect Freeware, the results log can be uploaded to a computer in a CSV format. DTC Connect can be used to set parameters in the wrench. You can change units of measure, modes of operation, degrees of fastener rotation, establish a target torque, minimum torque, maximum torque and more.

Five Modes of Operation

- **TAM:** Torque and Angle Monitoring identifies changing joint conditions and quickly identifies attempts to tightened previously tightened fasteners, or a "double hit."
- **T2A:** Torque to Angle (for highly engineered assemblies).
- **Track:** Displays torque values as torque is being applied. (No angle measurement).
- **Peak:** Provides the reading of the highest torque value created during torque application. (No angle measurement).
- **Residual:** Measures existing torque on previously tightened fasteners.

- ▶ Bi-directional accuracy $\pm 2\%$ indicated value from 20% to 100% of tool capacity.
- ▶ Meets or exceeds **ASME B107.300-2010** and **ISO 6789** requirements.
- ▶ All torque and angle settings can be set using buttons on wrench or DTC Connect freeware (coming August 2018).
- ▶ Built around SR's traditional pin/spring Dovetail you have access to over 200 one-piece interchangeable heads.
- ▶ Reversible square drive ratchet head included with wrench.
- ▶ Head length is adjustable via keypad. Uses 1 7/16" (36.5 mm) or 3 7/8" (98.4 mm) and maintains common center line.*
- ▶ Visible from any angle, light bands on both sides of the wrench turn yellow, then green, the wrench beeps, and the handle vibrates when target torque is achieved.
- ▶ 3 AAA batteries included with wrench. Works with either rechargeable NiMH, or Lithium Ion, or Alkaline batteries.
- ▶ Target, minimum, and maximum torque entered via wrench keypad or DTC Connect freeware.
- ▶ Lockable settings (and presets), via 4-digit password.
- ▶ Torque units: in lb, ft lb, Nm, cNm, cmkg, mkg.
- ▶ 99 presets, numbered 01-99, optionally named via serial command with up to 16-character names.
- ▶ Results log large enough for even the busiest assemblies. Export results in .csv format via mini-USB port.
- ▶ New, smaller profile fits in more places with light-weight, rugged design.
- ▶ Comes with free Certificate of Compliance from SR's **ISO/IEC 17025 Accredited Laboratory**.

DTC								Accuracy $\pm 2\%$
Model	Item No.	Torque Range*			Lever L mm	Ovl Length mm	Weight kg	Included Head
		lbf-ft	N-m	lbf-in				
DTC-4	R10680	0.8 - 4	1.1 - 5.4	10 - 50	352	402	0.47	SDRT 1/4
DTC-25	R10681	5 - 25	6.8 - 33.9	60 - 300	378	432	0.52	SDRT 3/8
DTC-75	R10682	15 - 75	20 - 101	180 - 900	419	473	0.59	SDRT 3/8
DTC-150	R10683	30 - 150	41 - 203	360 - 1800	502	562	0.68	SDRT 1/2
DTC-250	R10684	50 - 250	68 - 339	600 - 3000	703	762	0.99	SDRT 1/2
DTC-5	R10685	1 - 5	1.4 - 6.8	12 - 60	352	402	0.47	SDRT 1/4
DTC-80	R10686	16 - 80	22 - 108	192 - 960	419	473	0.59	SDRT 3/8

* DTC wrenches are calibrated for use with heads having 1 7/16" (36.5 mm) common centerline. On request wrenches can be calibrated for 3 7/8" (98.4 mm) centerline. The DTC can change the common centerline head in the software setting and not have to recalibrate the tool.



Further
info on our
website.
24/7

TEL: +49(0)40 303 989 100 • FAX: +49(0)40 303 989 101 • MAIL: info@zemo-tools.de

ZEMO
www.zemo-tools.de