

Direct Indicating Torque Wrench – M (Flat Beam)



Flat Beam Wrench with Memory Pointer

The four most important requirements of a torque wrench, accuracy, reliability, durability, and low ownership cost, are combined into these exceptional tools. Accuracy is literally ground into the wrench.

The special alloy steel beam is ground to a rate of deflection with the use of dead weights, rather than a dimensional tolerance. This process is time consuming and very labor intensive, but the result is a tool that remains accurate as long as the beam is intact and the pointer is on zero under no-load condition.

The flat shape of the beam insures the wrench remains at a right angle to the fastener, reducing or eliminating side-loading error. This unique taper-grinding distributes stress evenly along the entire length of the beam, extending tool life indefinitely.

With a minimum of moving parts, these tools are virtually repair and maintenance free.

For most models of this series 'M' a NATO approval (NSN) is available.

INFO

- ▶ Bi-directional accuracy of $\pm 2\%$ i.v. from 20% to 100% of rated capacity.
- ▶ Meets or exceeds requirements of ASME B107.300-2010 and EN ISO 6789.
- ▶ Ideal for prevailing-torque and destructive testing applications.
- ▶ Memory pointers indicate peak torque.
- ▶ Low mass/low inertia design of pointers helps eliminate reading distortion.
- ▶ Pivoted handle concentrates load at a precise lever to assure torque accuracy.
- ▶ Includes FREE certificate of calibration from SR's ISO/IEC 17025 Accredited Calibration Laboratory!

Flat Beam Series M

Accuracy $\pm 2\%$

Model	Item No.	Torque Range *				Graduation				SqD inch	Grip	L mm	Weight kg
		cN-m	N-m	lbf-in	lbf-ft	cN-m	N-m	lbf-in	lbf-ft				
M-110 cNm	R 855276	11 - 110	-	-	-	5	-	-	-	1/4	K	152	0.11
M-2.5 Nm	R 855281	-	0.25 - 2.5	-	-	-	0.1	-	-	3/8	K	159	0.16
M-5 Nm	R 855282	-	0.5 - 5	-	-	-	0.2	-	-	3/8	K	152	0.16
M-12 Nm	R 855283	-	1.2 - 12	-	-	-	0.5	-	-	K	B	165	0.17
M-22 Nm	R 855284	-	2.2 - 22	-	-	-	1	-	-	3/8	B	229	0.23
M-34 Nm	R 855285	-	3.4 - 34	-	-	-	1	-	-	3/8	B	343	1.2
M-70 Nm	R 855287	-	7 - 70	-	-	-	2	-	-	3/8	B	343	1.2
M-70 Nm - 1/2	R 855288	-	7 - 70	-	-	-	2	-	-	1/2	B	343	1.2
M-140 Nm	R 855289	-	14 - 140	-	-	-	5	-	-	1/2	B	381	1.3
M-210 Nm	R 855290	-	21 - 210	-	-	-	10	-	-	1/2	B	457	1.7
M-410 Nm	R 855292	-	41 - 410	-	-	-	10	-	-	3/4	B	762	4.9
M-10i	R 850188	-	-	1 - 10	-	-	-	0.5	-	1/4	K	152	0.11
M-25i	R 850222	-	-	2.5 - 25	-	-	-	1	-	3/8	K	159	0.16
M-50i	R 850242	-	-	5 - 50	-	-	-	2	-	3/8	K	152	0.16
M-100i	R 850191	-	-	10 - 100	-	-	-	5	-	3/8	K	165	0.17
M-200i	R 850211	-	-	20 - 200	-	-	-	10	-	3/8	B	229	0.23
M-300i	R 850228	-	-	30 - 300	-	-	-	10	-	3/8	B	343	1.2
M-600i	R 850246	-	-	60 - 600	-	-	-	25	-	3/8	B	343	1.2
M-600i - 1/2	R 850247	-	-	60 - 600	-	-	-	25	-	1/2	B	343	1.2
M-1200i	R 850195	-	-	120 - 1200	-	-	-	50	-	1/2	B	381	1.3
M-1800i	R 850205	-	-	180 - 1800	-	-	-	50	-	1/2	B	457	1.7
M-25	R 850220	-	-	-	2.5 - 25	-	-	-	1	3/8	B	343	1.2
M-50	R 850240	-	-	-	5 - 50	-	-	-	2	3/8	B	343	1.2
M-50 - 1/2	R 850241	-	-	-	5 - 50	-	-	-	2	1/2	B	343	1.2
M-100	R 850190	-	-	-	10 - 100	-	-	-	5	1/2	B	381	1.3
M-150	R 850198	-	-	-	15 - 150	-	-	-	5	1/2	B	457	1.7
M-300	R 850227	-	-	-	30 - 300	-	-	-	10	3/4	B	762	4.9

* NOTE: The torque output of this series is not affected by the position of the hand. However, adding a crowfoot adapter changes the lever length of the tool and must be taken into account in the torque equation to ensure accuracy.

