



Container for the FRL series

for series	Container for lubricators	Container for filters				O-ring for lubricator or filter
		Polycarbonate	Polycarbonate with automatic drain	Nylon	Metal	
20	C2SL-A	C2SF-A	AD27-C-A	C2SF-6-A	C2SF-2-A	C2FP-260S
30	C3SL-A	C3SF-A	AD37-A	C3SF-6-A	C3SF-2-A	C3FP-260S
40	C4SL-A	C4SF-A	AD47-A	C4SF-6-A	C4SF-2-A	C42FP-260S
50	C4SL-A	C4SF-A	AD47-A	C4SF-6-A	C4SF-2-A	C42SFP-260S
60	C4SL-A	C4SF-A	AD47-A	C4SF-6-A	C4SF-2-A	C42SFP-260S

In the case of the most severe, mechanical and/or chemical stress, it is recommended to use metal containers, which offer a very high level of protection (a.A.). Polycarbonate containers can be attacked by certain acids.



Modular designs – Assemblies

for series	Connect. inch	Spacer	Spacer with fastener	Intermediate outlet	End piece
20	1/4	Y200-A	Y200T-A	Y210-F02-A	E200-F02-A
30	3/8	Y300-A	Y300T-A	Y310-F02-A	E300-F03-A
40	1/2	Y400-A	Y400T-A	Y410-F03-A	E400-F04-A
40	3/4	Y500-A	Y500T-A	Y500-F03-A	E500-F06-A
50	3/4	Y600-A	Y600T-A	Y610-F04-A	E600-F06
50	1	Y600-A	Y600T-A	Y610-F04-A	E600-F10
60	3/4	Y600-A	Y600T-A	Y610-F04-A	E600-F6
60	1	Y600-A	Y600T-A	Y610-F04-A	E600-F10

Pipe connections for easy (dis)assembly of the modular combinations.

Intermediate pieces with fastening element for wall mounting of the modular combinations.

Intermediate pieces for connecting the combinations without wall mounting.

Mounting brackets for fixing the separate components can be found with the respective product series.

EAD – automatic condensate drain

Type	for series	Connect. inch	Control	Flow rate l/min	Noise filter	Operating pressure MPa	Ø mm
AD402-F02C-A	–	1/4	pneum.	–	–	–	–
AD402-F03D-A	–	3/8	pneum.	–	–	–	–
AD402-F04D-A	–	1/2	pneum.	–	–	–	–
EAD600-F10	–	1	pneum.	–	–	–	–
ADM200-045	–	1/2	electr. (220V)	–	–	–	–



AKM – Intermediate outlet with check valve

Type	for series	Connect. inch	Control	Flow rate l/min	Noise filter	Operating pressure MPa	Ø mm
AKM2000-F02-A	20	1/4	–	750	–	–	–
AKM3000-F02-A	30	3/8	–	1700	–	–	–
AKM4000-F03-A	40	1/2	–	3150	–	–	–



VHS – Manual shut-off valve

Type	for series	Connect. inch	Control	Flow rate l/min	Noise filter	Operating pressure MPa	Ø mm
VHS20-F02-A	20	1/4	–	750	AN103-01	–	–
VHS30-F03-A	30	3/8	–	1700	AN200-02	–	–
VHS40-F04-A	40	1/2	–	3150	AN300-03	–	–



K – External pressure gauges

Type	for series	Connect. inch	Control	Flow rate l/min	Noise filter	Operating pressure MPa	Ø mm
KB-10-40	20/30	1/8	–	–	–	0 - 1	40
KB-10-50	40/50/60	1/4	–	–	–	0 - 1	50



GC – internal pressure gauges for AR/RW series

Type	for series	Connect. inch	Sontrol	Flow rate l/min	Noise filter	Operating pressure MPa	Ø mm
G27-10-R1	10	1/16	–	–	–	0 - 1	26
GC3-10AS	20/30/40/50/60	–	–	–	–	0 - 1	24



ISE35 – Integrated pressure gauge with pressure switch and cable

Type	for series	Supply voltage	Cable length m	Degree of protection	Display	Set pressure range MPa	outlet
ISE35-N-65-LA	20/30/40/50/60	12-24V DC	2	IP40	2-farb. LED	-0,01 - 1	PNP
ISE35-N-25-LA	20/30/40/50/60	12-24V DC	2	IP40	2-farb. LED	-0,01 - 1	NPN



Loose filter elements for AF/AW series

Series	Standard 5 µm
20	AF20P-060S
30	AF30P-060S
40	AF40P-060S
50	AF50P-060S
60	AF60P-060S

AN – Noise filter

Series	Connect.
AN10-01	1/8
AN20-02	1/4
AN30-03	3/8
AN40-04	1/2
AN500-05	3/4
AN600-10	1
AN700-12	1 1/4
AN800-14	1 1/2



Further information available 24 / 7 on our website.