



Verbindungssteile mit Spindelführung – für Impulsschrauber



Verlängerungen – mit Stiftloch

Modell	Best.-Nr.	4kt Zoll	Form	L mm	D1 mm	D2 mm	L2 mm
KHV 3/8-75	312010	3/8	F	75	–	22	–
KHV 3/8-125	312011	3/8	F	125	–	22	–
KHV 3/8-250	312012	3/8	F	250	–	22	–
KHV 1/2-75	312013	1/2	F	75	–	25	–
KHV 1/2-125	312014	1/2	F	125	–	25	–
KHV 1/2-175	312015	1/2	F	175	–	25	–
KHV 1/2-250	312016	1/2	F	250	–	25	–
KHV 3/4-175	312017	3/4	F	175	–	44	–
KHV 3/4-250	312018	3/4	F	250	–	44	–
KHV 3/4-330	312019	3/4	F	330	–	44	–

Schnellwechselhalter

Modell	Best.-Nr.	E Zoll	A Zoll	L mm	D1 mm	D2 mm	L2 mm
KHQC3/8-3/8	314511	3/8	3/8	75	–	19	–
KHQC3/8-3/8L	314514	3/8	3/8	100	–	19	–
KHQC3/8-1/2	314509	3/8	1/2	80	–	20	–
KHQC1/2-3/8	314512	1/2	3/8	75	–	25	–
KHQC1/2-1/2	314513	1/2	1/2	100	–	25	–
KHQC3/4-1/2	314510	3/4	1/2	90	–	44	–
KHQC3/4-3/4	314515	3/4	3/4	125	–	44	–



Bithalter

Modell	Best.-Nr.	E Zoll	A Zoll	L mm	D1 mm	D2 mm	L2 mm
KHQC3/8-H1/4	313585	3/8	1/4	52	–	22	–
KHQC3/8-H7/16	313591	3/8	7/16	62	–	22	–
KHQC1/2-H1/4	313583	1/2	1/4	60	–	25	–
KHQC1/2-H7/16	313593	1/2	7/16	70	–	25	–
KHQC3/4-H7/16	313595	3/4	7/16	80	–	44	–



Gummiring und Sicherungstift

Modell	Best.-Nr.	4kt Zoll	Form	L mm	D1 mm	D2 mm	L2 mm
RS-3/8	222050	3/8	–	–	–	–	–
RS-1/2	240510	1/2	–	–	–	–	–
RS-3/4	250810	3/4	–	–	–	–	–



Weitere Infos
rund um die
Uhr auf unserer
Website.

Form F

