




Bits with 1/4" hexagonal drive DIN 3126 / ISO 1173 - C 6.3 *




Hexalobular Torx® – tough

Model	Item No.	TX #	L mm	Ø mm	Pk
T10-C6.3-18	113001	10	18	4	10
T15-C6.3-18	113002	15	18	4	10
T20-C6.3-18	113003	20	18	5	10
T25-C6.3-18	113004	25	18	5	10
T30-C6.3-18	113005	30	18	6	10
T40-C6.3-18	113006	40	18	6.3	10
T5-C6.3-25	113010	5	25	3	10
T6-C6.3-25	113011	6	25	3	10
T7-C6.3-25	113012	7	25	3	10
T8-C6.3-25	113013	8	25	3	10
T9-C6.3-25	113014	9	25	3	10
T10-C6.3-25	113015	10	25	4	10
T15-C6.3-25	113016	15	25	4	10
T20-C6.3-25	113017	20	25	5	10
T25-C6.3-25	113018	25	25	5	10
T27-C6.3-25	113019	27	25	6	10
T30-C6.3-25	113020	30	25	6	10
T40-C6.3-25	113021	40	25	6.3	10
T45-C6.3-25	113022	45	25	8	10
T50-C6.3-25	113023	50	25	9	10
T9-C6.3-50	113030	9	50	3	10
T10-C6.3-50	113031	10	50	3	10
T15-C6.3-50	113032	15	50	4	10
T20-C6.3-50	113033	20	50	4.5	10
T25-C6.3-50	113034	25	50	6	10
T27-C6.3-50	113035	27	50	6	10
T30-C6.3-50	113036	30	50	6	10
T40-C6.3-50	113037	40	50	6.3	10



Hexalobular Torx® – IMP

Model	Item No.	TX #	L mm	Ø mm	Pk
T10-C6.3-25-IMP	113040	10	25	4	10
T15-C6.3-25-IMP	113041	15	25	4	10
T20-C6.3-25-IMP	113042	20	25	5	10
T25-C6.3-25-IMP	113043	25	25	5	10
T30-C6.3-25-IMP	113044	30	25	6	10
T40-C6.3-25-IMP	113045	40	25	6.3	10



Hexalobular Torx® – CR

Model	Item No.	TX #	L mm	Ø mm	Pk
T5-C6.3-25-CR	113070	5	25	3	10
T6-C6.3-25-CR	113071	6	25	3	10
T7-C6.3-25-CR	113072	7	25	3	10
T8-C6.3-25-CR	113073	8	25	3	10
T9-C6.3-25-CR	113074	9	25	3	10
T10-C6.3-25-CR	113075	10	25	4	10
T15-C6.3-25-CR	113076	15	25	4	10
T20-C6.3-25-CR	113077	20	25	5	10
T25-C6.3-25-CR	113078	25	25	5	10
T27-C6.3-25-CR	113079	27	25	6	10
T30-C6.3-25-CR	113080	30	25	6	10
T40-C6.3-25-CR	113081	40	25	6.3	10
T50-C6.3-25-CR	113082	50	25	9	10



Hexalobular Torx® – ZRN

Model	Item No.	TX #	L mm	Ø mm	Pk
T10-C6.3-25-ZRN	113050	10	25	4	10
T15-C6.3-25-ZRN	113051	15	25	4	10
T20-C6.3-25-ZRN	113052	20	25	5	10
T25-C6.3-25-ZRN	113053	25	25	5	10
T27-C6.3-25-ZRN	113054	27	25	6	10
T30-C6.3-25-ZRN	113055	30	25	6	10
T40-C6.3-25-ZRN	113056	40	25	6.3	10
T10-C6.3-50-ZRN	113060	10	50	3	10
T15-C6.3-50-ZRN	113061	15	50	4	10
T20-C6.3-50-ZRN	113062	20	50	4.5	10
T25-C6.3-50-ZRN	113063	25	50	6	10
T30-C6.3-50-ZRN	113064	30	50	6	10
T40-C6.3-50-ZRN	113065	40	50	6.3	10





Bits with 1/4" hexagonal drive DIN 3126 / ISO 1173 - C 6.3 *




Hexalobular Torx® Ball – tough

Model	Item No.	TK #	L mm	Ø mm	Pk
TK10-C6.3-25	113410	10	25	–	10
TK15-C6.3-25	113411	15	25	–	10
TK20-C6.3-25	113412	20	25	–	10
TK25-C6.3-25	113413	25	25	–	10
TK27-C6.3-25	113414	27	25	–	10
TK30-C6.3-25	113415	30	25	–	10
TK40-C6.3-25	113416	40	25	–	10



Hexalobular Torx® Tamper-Resistant – ZRN

Model	Item No.	TR #	L mm	Ø mm	Pk
TR8-C6.3-25-ZRN	114050	8	25	3	10
TR10-C6.3-25-ZRN	114051	10	25	4	10
TR15-C6.3-25-ZRN	114052	15	25	4	10
TR20-C6.3-25-ZRN	114053	20	25	5	10
TR25-C6.3-25-ZRN	114054	25	25	5	10
TR27-C6.3-25-ZRN	114055	27	25	6	10
TR30-C6.3-25-ZRN	114056	30	25	6	10
TR40-C6.3-25-ZRN	114057	40	25	6.3	10




Hexalobular Torx® Tamper-Resistant – tough

Model	Item No.	TR #	L mm	Ø mm	Pk
TR7-C6.3-25	114010	7	25	3	10
TR8-C6.3-25	114011	8	25	3	10
TR9-C6.3-25	114012	9	25	3	10
TR10-C6.3-25	114013	10	25	4	10
TR15-C6.3-25	114014	15	25	4	10
TR20-C6.3-25	114015	20	25	5	10
TR25-C6.3-25	114016	25	25	5	10
TR27-C6.3-25	114017	27	25	6	10
TR30-C6.3-25	114018	30	25	6	10
TR40-C6.3-25	114019	40	25	6.3	10
TR45-C6.3-35	114020	45	35	–	10



Hexalobular Torx Plus® IP – tough

Model	Item No.	IP #	L mm	Ø mm	Pk
IP5-C6.3-25	113710	5	25	–	10
IP6-C6.3-25	113711	6	25	–	10
IP7-C6.3-25	113712	7	25	–	10
IP8-C6.3-25	113713	8	25	–	10
IP9-C6.3-25	113714	9	25	–	10
IP10-C6.3-25	113715	10	25	–	10
IP15-C6.3-25	113716	15	25	–	10
IP20-C6.3-25	113717	20	25	–	10
IP25-C6.3-25	113718	25	25	–	10
IP27-C6.3-25	113719	27	25	–	10
IP30-C6.3-25	113720	30	25	–	10
IP40-C6.3-25	113721	40	25	–	10



Hexalobular Torx® Tamper-Resistant – CR

Model	Item No.	TR #	L mm	Ø mm	Pk
TR7-C6.3-25-CR	114070	7	25	3	10
TR8-C6.3-25-CR	114071	8	25	3	10
TR9-C6.3-25-CR	114072	9	25	3	10
TR10-C6.3-25-CR	114073	10	25	4	10
TR15-C6.3-25-CR	114074	15	25	4	10
TR20-C6.3-25-CR	114075	20	25	5	10
TR25-C6.3-25-CR	114076	25	25	5	10
TR27-C6.3-25-CR	114077	27	25	6	10
TR30-C6.3-25-CR	114078	30	25	6	10
TR40-C6.3-25-CR	114079	40	25	6.3	10



Security Torx Plus® IPR – tough

Model	Item No.	IPR #	L mm	Ø mm	Pk
IPR10-C6.3-25	113610	10	25	–	10
IPR15-C6.3-25	113611	15	25	–	10
IPR20-C6.3-25	113612	20	25	–	10
IPR25-C6.3-25	113613	25	25	–	10
IPR27-C6.3-25	113616	27	25	–	10
IPR30-C6.3-25	113614	30	25	–	10
IPR40-C6.3-25	113615	40	25	–	10



For more info, visit our website.

24/7

* In combination with universal bit holder or for direct machine connection, see table „Assignment of tool drive and machine“ p. 72.

Mail: info@zemo-tools.de • Phone: +49 (0)40 303 989 100 • Web: www.zemo-tools.de

ZEMO
www.zemo-tools.de