





Bits mit 1/4" Sechskantantrieb DIN 3126 / ISO 1173 – C6.3 *



Sechsrund Torx® – zähhart

Modell	Best.-Nr.	TX #	L mm	Ø mm	VE
C6.3-T10-18	113001	10	18	4	10
C6.3-T15-18	113002	15	18	4	10
C6.3-T20-18	113003	20	18	5	10
C6.3-T25-18	113004	25	18	5	10
C6.3-T30-18	113005	30	18	6	10
C6.3-T40-18	113006	40	18	6,3	10
C6.3-T5-25	113010	5	25	3	10
C6.3-T6-25	113011	6	25	3	10
C6.3-T7-25	113012	7	25	3	10
C6.3-T8-25	113013	8	25	3	10
C6.3-T9-25	113014	9	25	3	10
C6.3-T10-25	113015	10	25	4	10
C6.3-T15-25	113016	15	25	4	10
C6.3-T20-25	113017	20	25	5	10
C6.3-T25-25	113018	25	25	5	10
C6.3-T27-25	113019	27	25	6	10
C6.3-T30-25	113020	30	25	6	10
C6.3-T40-25	113021	40	25	6,3	10
C6.3-T45-25	113022	45	25	8	10
C6.3-T50-25	113023	50	25	9	10
C6.3-T9-50	113030	9	50	3	10
C6.3-T10-50	113031	10	50	3	10
C6.3-T15-50	113032	15	50	4	10
C6.3-T20-50	113033	20	50	4,5	10
C6.3-T25-50	113034	25	50	6	10
C6.3-T27-50	113035	27	50	6	10
C6.3-T30-50	113036	30	50	6	10
C6.3-T40-50	113037	40	50	6,3	10



Sechsrund Torx® – IMP

Modell	Best.-Nr.	TX #	L mm	Ø mm	VE
C6.3-T10-25-IMP	113040	10	25	4	10
C6.3-T15-25-IMP	113041	15	25	4	10
C6.3-T20-25-IMP	113042	20	25	5	10
C6.3-T25-25-IMP	113043	25	25	5	10
C6.3-T30-25-IMP	113044	30	25	6	10
C6.3-T40-25-IMP	113045	40	25	6,3	10


Sechsrund Torx® – CR

Modell	Best.-Nr.	TX #	L mm	Ø mm	VE
C6.3-T5-25-CR	113070	5	25	3	10
C6.3-T6-25-CR	113071	6	25	3	10
C6.3-T7-25-CR	113072	7	25	3	10
C6.3-T8-25-CR	113073	8	25	3	10
C6.3-T9-25-CR	113074	9	25	3	10
C6.3-T10-25-CR	113075	10	25	4	10
C6.3-T15-25-CR	113076	15	25	4	10
C6.3-T20-25-CR	113077	20	25	5	10
C6.3-T25-25-CR	113078	25	25	5	10
C6.3-T27-25-CR	113079	27	25	6	10
C6.3-T30-25-CR	113080	30	25	6	10
C6.3-T40-25-CR	113081	40	25	6,3	10
C6.3-T50-25-CR	113082	50	25	9	10



Sechsrund Torx® – ZRN

Modell	Best.-Nr.	TX #	L mm	Ø mm	VE
C6.3-T10-25-ZRN	113050	10	25	4	10
C6.3-T15-25-ZRN	113051	15	25	4	10
C6.3-T20-25-ZRN	113052	20	25	5	10
C6.3-T25-25-ZRN	113053	25	25	5	10
C6.3-T27-25-ZRN	113054	27	25	6	10
C6.3-T30-25-ZRN	113055	30	25	6	10
C6.3-T40-25-ZRN	113056	40	25	6,3	10
C6.3-T10-50-ZRN	113060	10	50	3	10
C6.3-T15-50-ZRN	113061	15	50	4	10
C6.3-T20-50-ZRN	113062	20	50	4,5	10
C6.3-T25-50-ZRN	113063	25	50	6	10
C6.3-T30-50-ZRN	113064	30	50	6	10
C6.3-T40-50-ZRN	113065	40	50	6,3	10





Bits mit 1/4" Sechskantantrieb DIN 3126 / ISO 1173 – C6.3 *



Sechsrund Torx® Kugelkopf – zähhart

Modell	Best.-Nr.	TK #	L mm	Ø mm	VE
C6.3-TK10-25	113410	10	25	–	10
C6.3-TK15-25	113411	15	25	–	10
C6.3-TK20-25	113412	20	25	–	10
C6.3-TK25-25	113413	25	25	–	10
C6.3-TK27-25	113414	27	25	–	10
C6.3-TK30-25	113415	30	25	–	10
C6.3-TK40-25	113416	40	25	–	10




Sechsrund Torx® Tamper-Resistant – ZRN

Modell	Best.-Nr.	TR #	L mm	Ø mm	VE
C6.3-TR8-25-ZRN	114050	8	25	3	10
C6.3-TR10-25-ZRN	114051	10	25	4	10
C6.3-TR15-25-ZRN	114052	15	25	4	10
C6.3-TR20-25-ZRN	114053	20	25	5	10
C6.3-TR25-25-ZRN	114054	25	25	5	10
C6.3-TR27-25-ZRN	114055	27	25	6	10
C6.3-TR30-25-ZRN	114056	30	25	6	10
C6.3-TR40-25-ZRN	114057	40	25	6,3	10




Sechsrund Torx® Tamper-Resistant – zähhart

Modell	Best.-Nr.	TR #	L mm	Ø mm	VE
C6.3-TR7-25	114010	7	25	3	10
C6.3-TR8-25	114011	8	25	3	10
C6.3-TR9-25	114012	9	25	3	10
C6.3-TR10-25	114013	10	25	4	10
C6.3-TR15-25	114014	15	25	4	10
C6.3-TR20-25	114015	20	25	5	10
C6.3-TR25-25	114016	25	25	5	10
C6.3-TR27-25	114017	27	25	6	10
C6.3-TR30-25	114018	30	25	6	10
C6.3-TR40-25	114019	40	25	6,3	10
C6.3-TR45-35	114020	45	35	–	10




Sechsrund Torx Plus® IP – zähhart

Modell	Best.-Nr.	IP #	L mm	Ø mm	VE
C6.3-IP5-25	113710	5	25	–	10
C6.3-IP6-25	113711	6	25	–	10
C6.3-IP7-25	113712	7	25	–	10
C6.3-IP8-25	113713	8	25	–	10
C6.3-IP9-25	113714	9	25	–	10
C6.3-IP10-25	113715	10	25	–	10
C6.3-IP15-25	113716	15	25	–	10
C6.3-IP20-25	113717	20	25	–	10
C6.3-IP25-25	113718	25	25	–	10
C6.3-IP27-25	113719	27	25	–	10
C6.3-IP30-25	113720	30	25	–	10
C6.3-IP40-25	113721	40	25	–	10




Sechsrund Torx® Tamper-Resistant – CR

Modell	Best.-Nr.	TR #	L mm	Ø mm	VE
C6.3-TR7-25-CR	114070	7	25	3	10
C6.3-TR8-25-CR	114071	8	25	3	10
C6.3-TR9-25-CR	114072	9	25	3	10
C6.3-TR10-25-CR	114073	10	25	4	10
C6.3-TR15-25-CR	114074	15	25	4	10
C6.3-TR20-25-CR	114075	20	25	5	10
C6.3-TR25-25-CR	114076	25	25	5	10
C6.3-TR27-25-CR	114077	27	25	6	10
C6.3-TR30-25-CR	114078	30	25	6	10
C6.3-TR40-25-CR	114079	40	25	6,3	10



5-Punkt Security Torx Plus® IPR – zähhart

Modell	Best.-Nr.	IPR #	L mm	Ø mm	VE
C6.3-IPR10-25	113610	10	25	–	10
C6.3-IPR15-25	113611	15	25	–	10
C6.3-IPR20-25	113612	20	25	–	10
C6.3-IPR25-25	113613	25	25	–	10
C6.3-IPR27-25	113616	27	25	–	10
C6.3-IPR30-25	113614	30	25	–	10
C6.3-IPR40-25	113615	40	25	–	10



Weitere Infos
auf unserer
Website.
24/7

* In Verbindung mit Universal-Bithalter oder für direkten Maschinenanschluss, vgl. Tabelle „Zuordnung von Werkzeugantrieb und Maschine“.

ZEMO
www.zemo-tools.de

TEL: +49 (0)40 303 989 100 • EML: info@zemo-tools.de • WEB: www.zemo-tools.de