



Bits with 1/4" hexagonal drive DIN 3126 / ISO 1173 - E 6.3 *



Slotted – tough

Model	Item No.	T mm	W mm	L mm	Ø mm	Pk
SL0.5x3.0-E6.3-50	110210	0.5	3.0	50	3	10
SL0.5x4.0-E6.3-50	110222	0.5	4.0	50	4	10
SL0.6x3.5-E6.3-50	110216	0.6	3.5	50	3.5	10
SL0.6x4.0-E6.3-50	110258	0.6	4.0	50	4	10
SL0.6x4.5-E6.3-50	110228	0.6	4.5	50	4.5	10
SL0.8x4.0-E6.3-50	110259	0.8	4.0	50	4	10
SL0.8x5.5-E6.3-50	110234	0.8	5.5	50	5.5	10
SL1.0x5.5-E6.3-50	110240	1.0	5.5	50	5.5	10
SL1.0x6.0-E6.3-50	110260	1.0	6.0	50	6	10
SL1.2x6.5-E6.3-50	110246	1.2	6.5	50	6.5	10
SL1.2x8.0-E6.3-50	110252	1.2	8.0	50	8	10
SL1.6x10-E6.3-50	110261	1.6	10	50	10	10
SL0.5x3.0-E6.3-70	110211	0.5	3.0	70	3	10
SL0.5x4.0-E6.3-70	110223	0.5	4.0	70	4	10
SL0.6x3.5-E6.3-70	110217	0.6	3.5	70	3.5	10
SL0.6x4.5-E6.3-70	110229	0.6	4.5	70	4.5	10
SL0.8x4.0-E6.3-70	110262	0.8	4.0	70	4	10
SL0.8x5.5-E6.3-70	110235	0.8	5.5	70	5.5	10
SL1.0x5.5-E6.3-70	110241	1.0	5.5	70	5.5	10
SL1.0x6.0-E6.3-70	110263	1.0	6.0	70	6	10
SL1.2x6.5-E6.3-70	110247	1.2	6.5	70	6.5	10
SL1.2x8.0-E6.3-70	110253	1.2	8.0	70	8	10
SL0.5x3.0-E6.3-90	110212	0.5	3.0	90	3	10
SL0.5x4.0-E6.3-90	110224	0.5	4.0	90	4	10
SL0.6x3.5-E6.3-90	110218	0.6	3.5	90	3.5	10
SL0.6x4.5-E6.3-90	110230	0.6	4.5	90	4.5	10
SL0.8x5.5-E6.3-90	110236	0.8	5.5	90	5.5	10
SL1.0x5.5-E6.3-90	110242	1.0	5.5	90	5.5	10
SL1.2x6.5-E6.3-90	110248	1.2	6.5	90	6.5	10
SL1.2x8.0-E6.3-90	110254	1.2	8.0	90	8	10



Crosshead Phillips® – IMP

Model	Item No.	PH #	L mm	Ø mm	Pk
PH2-E6.3-50-IMP	111282	2	50	6	10
PH3-E6.3-50-IMP	111283	3	50	6	10



Crosshead Phillips® – tough

Model	Item No.	PH #	L mm	Ø mm	Pk
PH0-E6.3-50	111209	0	50	4	10
PH1-E6.3-50	111210	1	50	4.5	10
PH2-E6.3-50	111216	2	50	6	10
PH3-E6.3-50	111222	3	50	6	10
PH4-E6.3-50	111228	4	50	6	10
PH0-E6.3-70	111234	0	70	4	10
PH1-E6.3-70	111211	1	70	4.5	10
PH2-E6.3-70	111217	2	70	6.0	10
PH3-E6.3-70	111223	3	70	6.3	10
PH1-E6.3-90	111212	1	90	4.5	10
PH2-E6.3-90	111218	2	90	6	10
PH3-E6.3-90	111224	3	90	6	10
PH1-E6.3-102	111213	1	102	4.5	10
PH2-E6.3-102	111219	2	102	6.0	10
PH3-E6.3-102	111225	3	102	6.3	10
PH1-E6.3-110	111235	1	110	4.5	10
PH2-E6.3-110	111237	2	110	6	10
PH3-E6.3-110	111239	3	110	6	10
PH1-E6.3-127	111214	1	127	4.5	10
PH2-E6.3-127	111220	2	127	6.0	10
PH3-E6.3-127	111226	3	127	6.3	10
PH1-E6.3-152	111215	1	152	4.5	10
PH2-E6.3-152	111221	2	152	6	10
PH3-E6.3-152	111227	3	152	6	10
PH2-E6.3-170	111236	2	170	6	
PH2-E6.3-200	111238	2	200	6	
PH2-E6.3-270	111240	2	270	8	
PH2-E6.3-300	111241	2	300	8	



Crosshead Phillips® – ZRN

Model	Item No.	PH #	L mm	Ø mm	Pk
PH1-E6.3-50-ZRN	111451	1	50	4.5	10
PH2-E6.3-50-ZRN	111454	2	50	6	10
PH3-E6.3-50-ZRN	111457	3	50	6	10
PH1-E6.3-70-ZRN	111452	1	70	4.5	10
PH2-E6.3-70-ZRN	111455	2	70	6	10
PH3-E6.3-70-ZRN	111458	3	70	6	10
PH1-E6.3-90-ZRN	111453	1	90	4.5	10
PH2-E6.3-90-ZRN	111456	2	90	6	10
PH3-E6.3-90-ZRN	111459	3	90	6	10

* In combination with universal bit holder or for direct machine connection, see table „Assignment of tool drive and machine“ p. 72.





Bits with 1/4" hexagonal drive DIN 3126 / ISO 1173 - E 6.3 *



Crosshead Pozidriv® – tough

Model	Item No.	PZ #	L mm	Ø mm	Pk
PZ0-E6.3-50	112201	0	50	4	10
PZ1-E6.3-50	112210	1	50	4.5	10
PZ2-E6.3-50	112216	2	50	6	10
PZ3-E6.3-50	112222	3	50	6	10
PZ4-E6.3-50	112228	4	50	10	10
PZ0-E6.3-70	112202	0	70	4	10
PZ1-E6.3-70	112211	1	70	4.5	10
PZ2-E6.3-70	112217	2	70	6	10
PZ3-E6.3-70	112223	3	70	6.3	10
PZ1-E6.3-90	112212	1	90	4.5	10
PZ2-E6.3-90	112218	2	90	6	10
PZ3-E6.3-90	112224	3	90	6.3	10
PZ1-E6.3-102	112229	1	102	4.5	10
PZ2-E6.3-102	112232	2	102	6	10
PZ3-E6.3-102	112235	3	102	6	10
PZ1-E6.3-110	112230	1	110	4.5	10
PZ2-E6.3-110	112233	2	110	6	10
PZ3-E6.3-110	112236	3	110	6	10
PZ1-E6.3-127	112231	1	127	4.5	10
PZ2-E6.3-127	112234	2	127	6	10
PZ3-E6.3-127	112237	3	127	6	10
PZ1-E6.3-152	112215	1	152	4.5	10
PZ2-E6.3-152	112221	2	152	6	10
PZ3-E6.3-152	112227	3	152	6	10



Crosshead Pozidriv® – ZRN

Model	Item No.	PH #	L mm	Ø mm	Pk
PZ1-E6.3-50-ZRN	112251	1	50	4.5	10
PZ2-E6.3-50-ZRN	112254	2	50	6	10
PZ3-E6.3-50-ZRN	112257	3	50	6	10
PZ1-E6.3-70-ZRN	112252	1	70	4.5	10
PZ2-E6.3-70-ZRN	112255	2	70	6	10
PZ3-E6.3-70-ZRN	112258	3	70	6	10
PZ1-E6.3-90-ZRN	112253	1	90	4.5	10
PZ2-E6.3-90-ZRN	112256	2	90	6	10
PZ3-E6.3-90-ZRN	112259	3	90	6	10



Crosshead Pozidriv® – IMP

Model	Item No.	PH #	L mm	Ø mm	Pk
PZ2-E6.3-50-IMP	112242	2	50	6	10
PZ3-E6.3-50-IMP	112243	3	50	6	10



Hexalobular Torx® – tough

Model	Item No.	TX #	L mm	Ø mm	Pk
T6-E6.3-50	113210	6	50	3	10
T7-E6.3-50	113260	7	50	3	10
T8-E6.3-50	113213	8	50	3	10
T9-E6.3-50	113265	9	50	3	10
T10-E6.3-50	113216	10	50	3	10
T15-E6.3-50	113222	15	50	4	10
T20-E6.3-50	113228	20	50	4,5	10
T25-E6.3-50	113234	25	50	6	10
T27-E6.3-50	113240	27	50	6	10
T30-E6.3-50	113246	30	50	6	10
T40-E6.3-50	113252	40	50	6,3	10
T50-E6.3-50	113270	50	50	8	10
T55-E6.3-50	113271	55	50	10	10
T6-E6.3-70	113211	6	70	3	10
T7-E6.3-70	113261	7	70	3	10
T8-E6.3-70	113214	8	70	3	10
T9-E6.3-70	113266	9	70	3	10
T10-E6.3-70	113217	10	70	3	10
T15-E6.3-70	113223	15	70	4	10
T20-E6.3-70	113229	20	70	4,5	10
T25-E6.3-70	113235	25	70	6	10
T27-E6.3-70	113241	27	70	6	10
T30-E6.3-70	113247	30	70	6	10
T40-E6.3-70	113253	40	70	6,3	10
T6-E6.3-90	113258	6	90	3	10
T7-E6.3-90	113262	7	90	3	10
T8-E6.3-90	113215	8	90	3	10
T9-E6.3-90	113267	9	90	3	10
T10-E6.3-90	113218	10	90	3	10
T15-E6.3-90	113224	15	90	4	10
T20-E6.3-90	113230	20	90	4,5	10
T25-E6.3-90	113236	25	90	6	10
T27-E6.3-90	113242	27	90	6	10
T30-E6.3-90	113248	30	90	6,0	10



For more
info, visit our
website.

24/7

* In combination with universal bit holder or for direct machine connection, see table „Assignment of tool drive and machine“ p. 72.

Mail: info@zemo-tools.de • Phone: +49 (0)40 303 989 100 • Web: www.zemo-tools.de

ZEMO
www.zemo-tools.de