



Bits mit 1/4" Sechskantantrieb DIN 3126 / ISO 1173 – E 6,3 *



Sechsrund Torx® – zähhart

Modell	Best.-Nr.	TX #	L mm	Ø mm	VE
E6.3-T6-50	113210	6	50	3	10
E6.3-T7-50	113260	7	50	3	10
E6.3-T8-50	113213	8	50	3	10
E6.3-T9-50	113265	9	50	3	10
E6.3-T10-50	113216	10	50	3	10
E6.3-T15-50	113222	15	50	4	10
E6.3-T20-50	113228	20	50	4,5	10
E6.3-T25-50	113234	25	50	6	10
E6.3-T27-50	113240	27	50	6	10
E6.3-T30-50	113246	30	50	6	10
E6.3-T40-50	113252	40	50	6,3	10
E6.3-T50-50	113270	50	50	8	10
E6.3-T55-50	113271	55	50	10	10
E6.3-T6-70	113211	6	70	3	10
E6.3-T7-70	113261	7	70	3	10
E6.3-T8-70	113214	8	70	3	10
E6.3-T9-70	113266	9	70	3	10
E6.3-T10-70	113217	10	70	3	10
E6.3-T15-70	113223	15	70	4	10
E6.3-T20-70	113229	20	70	4,5	10
E6.3-T25-70	113235	25	70	6	10
E6.3-T27-70	113241	27	70	6	10
E6.3-T30-70	113247	30	70	6	10
E6.3-T40-70	113253	40	70	6,3	10
E6.3-T6-90	113258	6	90	3	10
E6.3-T7-90	113262	7	90	3	10
E6.3-T8-90	113215	8	90	3	10
E6.3-T9-90	113267	9	90	3	10
E6.3-T10-90	113218	10	90	3	10
E6.3-T15-90	113224	15	90	4	10
E6.3-T20-90	113230	20	90	4,5	10
E6.3-T25-90	113236	25	90	6	10
E6.3-T27-90	113242	27	90	6	10
E6.3-T30-90	113248	30	90	6,0	10
E6.3-T40-90	113254	40	90	6,3	10
E6.3-T15-102	113225	15	102	4,0	10
E6.3-T20-102	113231	20	102	4,5	10
E6.3-T25-102	113237	25	102	6,0	10
E6.3-T30-102	113249	30	102	6,0	10
E6.3-T40-102	113255	40	102	6,3	10
E6.3-T10-127	113220	10	127	3,0	10
E6.3-T15-127	113226	15	127	4,0	10
E6.3-T20-127	113232	20	127	4,5	10
E6.3-T25-127	113238	25	127	6,0	10

Sechsrund Torx® – zähhart

Modell	Best.-Nr.	TX #	L mm	Ø mm	VE
E6.3-T27-127	113244	27	127	6,0	10
E6.3-T30-127	113250	30	127	6,0	10
E6.3-T40-127	113256	40	127	6,3	10
E6.3-T6-152	113259	6	152	3	10
E6.3-T7-152	113263	7	152	3	10
E6.3-T8-152	113264	8	152	3	10
E6.3-T9-152	113268	9	152	3	10
E6.3-T10-152	113221	10	152	3	10
E6.3-T15-152	113227	15	152	4	10
E6.3-T20-152	113233	20	152	4,5	10
E6.3-T25-152	113239	25	152	6	10
E6.3-T27-152	113245	27	152	6	10
E6.3-T30-152	113251	30	152	6	10
E6.3-T40-152	113257	40	152	6,3	10
E6.3-T45-152	113269	45	152	7	10
E6.3-T20-200	113272	20	200	4,5	
E6.3-T25-200	113273	25	200	6	
E6.3-T30-200	113276	30	200	6	
E6.3-T25-250	113274	25	250	6	
E6.3-T30-250	113277	30	250	6	
E6.3-T25-300	113275	25	300	6	
E6.3-T30-325	113278	30	325	6	
E6.3-T30-400	113279	25	400	6	



Sechsrund Torx® – ZRN

Modell	Best.-Nr.	TX #	L mm	Ø mm	VE
E6.3-T8-50-ZRN	113291	8	50	3	10
E6.3-T10-50-ZRN	113292	10	50	3	10
E6.3-T15-50-ZRN	113293	15	50	4	10
E6.3-T20-50-ZRN	113294	20	50	4,5	10
E6.3-T25-50-ZRN	113295	25	50	6	10
E6.3-T30-50-ZRN	113296	30	50	6	10
E6.3-T40-50-ZRN	113297	40	50	–	10





Bits mit 1/4" Sechskantantrieb DIN 3126 / ISO 1173 – E 6,3 *



Sechsrund Torx® – IMP

Modell	Best.-Nr.	TX #	L mm	Ø mm	VE
E6.3-T10-50-IMP	113281	10	50	3	10
E6.3-T15-50-IMP	113282	15	50	4	10
E6.3-T20-50-IMP	113283	20	50	4,5	10
E6.3-T25-50-IMP	113284	25	50	6	10
E6.3-T30-50-IMP	113285	30	50	6	10
E6.3-T40-50-IMP	113286	40	50	–	10




Sechsrund Torx Plus® IP – zähhart

Modell	Best.-Nr.	IP #	L mm	Ø mm	VE
E6.3-IP6-50	113601	6	50	3	10
E6.3-IP8-50	113603	8	50	3	10
E6.3-IP9-50	113605	9	50	3	10
E6.3-IP10-50	113607	10	50	3	10
E6.3-IP15-50	113609	15	50	4	10
E6.3-IP20-50	113611	20	50	4,5	10
E6.3-IP25-50	113613	25	50	6	10
E6.3-IP30-50	113615	30	50	6	10
E6.3-IP40-50	113617	40	50	–	10
E6.3-IP6-90	113602	6	90	3	10
E6.3-IP8-90	113604	8	90	3	10
E6.3-IP9-90	113606	9	90	3	10
E6.3-IP10-90	113608	10	90	3	10
E6.3-IP15-90	113610	15	90	4	10
E6.3-IP20-90	113612	20	90	4,5	10
E6.3-IP25-90	113614	25	90	6	10
E6.3-IP30-90	113616	30	90	6	10
E6.3-IP40-90	113618	40	90	–	10



Sechsrund Torx® Tamper-Resistant – zähhart

Modell	Best.-Nr.	TR #	L mm	Ø mm	VE
E6.3-TR8-50	114208	8	50	3	10
E6.3-TR9-50	114211	9	50	3	10
E6.3-TR10-50	114214	10	50	3	10
E6.3-TR15-50	114218	15	50	4	10
E6.3-TR20-50	114222	20	50	4,5	10
E6.3-TR25-50	114226	25	50	6	10
E6.3-TR27-50	114230	27	50	6	10
E6.3-TR30-50	114233	30	50	6	10
E6.3-TR40-50	114237	40	50	–	10
E6.3-TR8-70	114209	8	70	3	10
E6.3-TR9-70	114212	9	70	3	10
E6.3-TR10-70	114215	10	70	3	10
E6.3-TR15-70	114219	15	70	4	10
E6.3-TR20-70	114223	20	70	4,5	10
E6.3-TR25-70	114227	25	70	6	10
E6.3-TR27-70	114231	27	70	6	10
E6.3-TR30-70	114234	30	70	6	10
E6.3-TR40-70	114238	40	70	6,3	10
E6.3-TR8-90	114210	8	90	3	10
E6.3-TR9-90	114213	9	90	3	10
E6.3-TR10-90	114216	10	90	3	10
E6.3-TR15-90	114220	15	90	4	10
E6.3-TR20-90	114224	20	90	4,5	10
E6.3-TR25-90	114228	25	90	6	10
E6.3-TR27-90	114232	27	90	6	10
E6.3-TR30-90	114235	30	90	6,0	10
E6.3-TR40-90	114239	40	90	6,3	10
E6.3-TR10-152	114217	10	152	3	
E6.3-TR15-152	114221	15	152	4	
E6.3-TR20-152	114225	20	152	4,5	
E6.3-TR25-152	114229	25	152	6	
E6.3-TR30-152	114236	30	152	6	



Weitere Infos
auf unserer
Website.
24/7

* In Verbindung mit Kombi-Bithalter oder für direkten Maschinenanschluss,
vgl. Tabelle „Zuordnung von Werkzeugantrieb und Maschine“.

TEL: +49 (0)40 303 989 100 • EML: info@zemo-tools.de • WEB: www.zemo-tools.de

ZEMO
www.zemo-tools.de