




Nutsetter acc. DIN 7424 – with hexagon drive E 6.3 *



Drive E6.3 – Hexagon

Model	Item No.	A/F	L mm	L1 mm	D1 mm	Pk
NR4.5-E6.3-50	117210	4.5	50	3.0	7.7	5
NR5-E6.3-50	117211	5	50	4.0	8.4	5
NR5.5-E6.3-50	117212	5.5	50	4.0	9.0	5
NR6-E6.3-50	117213	6	50	4.5	10.0	5
NR1/4-E6.3-50	117222	1/4"	50	5.0	10.0	5
NR7-E6.3-50	117214	7	50	5.0	11.0	5
NR8-E6.3-50	117215	8	50	6.0	13.0	5
NR9-E6.3-50	117216	9	50	7.0	14.0	5
NR3/8-E6.3-50	117223	3/8"	50	7.0	14.2	5
NR10-E6.3-50	117217	10	50	7.0	14.2	5
NR11-E6.3-50	117218	11	50	8.0	16.0	5
NR12-E6.3-50	117219	12	50	8.0	17.0	5
NR13-E6.3-50	117220	13	50	8.0	18.0	5
NR14-E6.3-50	117221	14	50	9.0	19.0	5
NR4-E6.3-55	117050	4	55	4.5	8.0	5
NR6-E6.3-55	117052	6	55	4.5	10.0	5
NR7-E6.3-55	117053	7	55	5.0	11.0	5
NR8-E6.3-55	117054	8	55	5.0	12.0	5
NR10-E6.3-55	117056	10	55	6.5	14.0	5
NR4.5-E6.3-65	117410	4.5	65	3.0	7.7	5
NR5-E6.3-65	117411	5	65	4.0	8.4	5
NR5.5-E6.3-65	117412	5.5	65	4.0	9.0	5
NR6-E6.3-65	117413	6	65	5.0	5.2	5
NR1/4-E6.3-65	117421	1/4"	65	5.0	5.2	5
NR7-E6.3-65	117414	7	65	5.0	11.5	5
NR8-E6.3-65	117415	8	65	6.0	12.7	5
NR3/8-E6.3-65	117422	3/8"	65	7.0	14.5	5
NR10-E6.3-65	117417	5	65	7.0	16.0	5
NR13-E6.3-65	117420	13	65	8.0	18.0	5
NR6-E6.3-75	117430	6	75	4.5	5.0	5
NR7-E6.3-75	117431	7	75	4.5	11.0	5
NR8-E6.3-75	117432	8	75	4.5	12.0	5
NR10-E6.3-75	117434	5	75	5.5	14.0	5
NR12-E6.3-75	117436	12	75	5.5	17.0	5
NR13-E6.3-75	117437	13	75	5.5	18.0	5
NR14-E6.3-75	117438	14	75	5.5	19.0	5
NR12-E6.3-200	117442	12	200	5.5	17.0	
NR14-E6.3-200	117444	14	200	5.5	19.0	




Drive E6.3 – Hexagon w clamp spring

Model	Item No.	A/F	L mm	L1 mm	D1 mm	Pk
NRKF7-E6.3-50	117610	7	50	5.2	13	5
NRKF8-E6.3-50	117611	8	50	5.2	14	5
NRKF3/8-E6.3-50	117614	3/8"	50	5.2	16	5
NRKF10-E6.3-50	117612	10	50	5.2	16	5



Functional principle of the clamp spring

In order to hold non-magnetisable screws – e.g. stainless steel – securely in the tool when screwing, the required clamping effect is applied by a steel spring with a rounded tip. The rounded tip of the spring prevents damage to the coating applied, e.g. paint on facade screws.



Drive E6.3 – Hexalobular (Torx®)

Model	Item No.	TX #	L mm	L1 mm	D1 mm	Pk
NRE4-E6.3-50	117450	E4	50	3.5	6.5	5
NRE5-E6.3-50	117451	E5	50	4.1	7.7	5
NRE6-E6.3-50	117452	E6	50	4.3	8.7	5
NRE8-E6.3-50	117453	E8	50	6.0	9.7	5
NRE10-E6.3-50	117454	E10	50	7.0	12.2	5

