



**Sturtevant
Richmont**



Handle Adjustments

Adjustable Screwdriver

P Series

- Exceptionally smooth rotation
- Ergonomically friendly: requires only 18 degrees of rotation to achieve preset torque value. Other brands require 36 degrees, 45 degrees, or even 60 degrees to achieve target torque
- Perfect for assembly of electronic components and precision mechanical products!
- Ideal for use in field maintenance kits - electro-static discharge compliant when ESD practices are used.
- Clutch releases automatically when preset torque attained - no overtorquing.
- Anti-backlash design for repeatability
- Long shaft allows operator to reach limited-access applications
- Accuracy of +/- 6% (from 20% to 100% of capacity) meets or exceeds ASME B107.300 - 2010 and ISO 6789 requirements
- Bi-directional versatility - CW and CCW operation
- Uses standard bits, adapters, and sockets

Color code all your screwdrivers

When you place your order, just mention you want colors and we will send a package of five easy-to-apply heat shrink sleeves. Color code bands are 1/2" in length.



Specifications

Capacity

Length (less bit)
Grip Diameter
Grip Length
Weight
Drive Size

6-2H

Part No. 810511
20-100 in. oz.
1.25-6.25 in. lb.
6"
1.57"
4.43"
0.5 lb.
1/4" Female Hex

20-2H

Part No. 810512
40-240 in. oz.
4-20 in. lb.
6"
1.57"
4.43"
0.5 lb.
1/4" Female Hex

40-2H

Part No. 810513
115.2-576 in. oz.
5-40 in. lb.
6"
1.57"
4.43"
0.5 lb.
1/4" Female Hex

Part No.	Package Contents
816734	Multi-color (1 each)
816735	Blue (5)
816736	Yellow (5)
816737	Red (5)
816738	White (5)
816739	Green (5)

WARNING



- Do not exceed rated torque
- Do not use to break fasteners loose
- Periodic recalibration is necessary to maintain accuracy
- Read safety precautions on page 61