

Power Sockets with 1.5" square drive according to DIN 3121 H 40



Hex Driver – normal

Model	Item No.	A/F mm	L mm	D1 mm	D2 mm	L1 mm	Pk
K1.1/2-A19	270158	19	105	–	86	20	–
K1.1/2-A22	270159	22	105	–	86	20	–
K1.1/2-A24	270160	24	105	–	86	20	–
K1.1/2-A27	270161	27	105	–	86	20	–
K1.1/2-A30	270162	30	105	–	86	20	–
K1.1/2-A32	270163	32	105	–	86	20	–
K1.1/2-A33	270164	33	105	–	86	20	–
K1.1/2-A36	270174	36	105	–	86	20	–
K1.1/2-A38	270175	38	105	–	86	20	–
K1.1/2-A41	270157	41	105	–	86	20	–
K1.1/2-A46	270165	46	105	–	86	20	–
K1.1/2-A50	270166	50	105	–	86	20	–
K1.1/2-A55	270167	55	105	–	86	20	–

Rubber ring & locking pin

Model	Item No.	Size inch	–	D1 mm	D2 mm	–	Pk
RS-1.1/2	270210	1 1/2	–	–	86	–	5
D01112-0-095	270211	1 1/2	–	–	95	–	5
D01112-0-127	270212	1 1/2	–	–	127	–	5



Hex driver (Allen) – deep

Model	Item No.	A/F mm	L mm	D1 mm	D2 mm	L1 mm	Pk
K1.1/2-A19-L	270150	19	120	–	86	20	–
K1.1/2-A22-L	270151	22	120	–	86	20	–
K1.1/2-A24-L	270152	24	120	–	86	20	–
K1.1/2-A27-L	270153	27	120	–	86	20	–
K1.1/2-A30-L	270154	30	120	–	86	24	–
K1.1/2-A32-L	270155	32	120	–	86	24	–
K1.1/2-A33-L	270168	33	120	–	86	24	–
K1.1/2-A36-L	270156	36	120	–	86	28	–
K1.1/2-A38-L	270169	38	120	–	86	28	–
K1.1/2-A41-L	270170	41	120	–	86	34	–
K1.1/2-A46-L	270171	46	120	–	86	38	–
K1.1/2-A50-L	270172	50	120	–	86	38	–
K1.1/2-A55-L	270173	55	120	–	86	43	–

