

## Power Sockets with 1" square drive according to DIN 3121 H 25



### Holder & interchangeable hex bits

Model	Item No.	A/F mm	L mm	D1 mm	D2 mm	T mm	Pk
K1-AWE22	260750	22	70	44.0	54	-	-
AWE22-A14	260810	14	50	-	-	-	-
AWE22-A17	260811	17	50	-	-	-	-
AWE22-A19	260812	19	50	-	-	-	-
AWE22-A22	260813	22	50	-	-	-	-
AWE22-A24	260814	24	50	-	-	-	-
AWE22-A27	260815	27	50	-	-	-	-
AWE22-A30	260816	30	50	-	-	-	-
AWE22-A32	260817	32	50	-	-	-	-
AWE22-A36	260818	36	50	-	-	-	-

### Hex driver (Allen) – deep

Model	Item No.	A/F mm	L mm	D1 mm	D2 mm	L1 mm	Pk
K1-A10-L	260710	10	100	-	54	20	-
K1-A12-L	260711	12	100	-	54	20	-
K1-A14-L	260712	14	100	-	54	20	-
K1-A17-L	260713	17	100	-	54	20	-
K1-A19-L	260714	19	100	-	54	20	-
K1-A22-L	260715	22	100	-	54	20	-
K1-A24-L	260717	24	100	-	54	20	-
K1-A27-L	260718	27	100	-	54	20	-
K1-A30-L	260719	30	100	-	54	24	-
K1-A32-L	260720	32	100	-	54	24	-
K1-A36-L	260722	36	100	-	54	28	-
K1-A22-EL	260716	22	140	-	54	20	-



### Hex driver (Allen) – normal

Model	Item No.	A/F mm	L mm	D1 mm	D2 mm	L1 mm	Pk
K1-A14	260649	14	75	-	54	12	-
K1-A17	260650	17	75	-	54	15	-
K1-A19	260651	19	75	-	54	17	-
K1-A22	260652	22	75	-	54	20	-
K1-A24	260653	24	75	-	54	20	-
K1-A27	260654	27	75	-	54	20	-
K1-A30	260655	30	75	-	54	20	-
K1-A32	260656	32	75	-	54	20	-
K1-A36	260657	36	75	-	54	20	-

### Rubber ring & locking pin

Model	Item No.	Size inch	-	D1 mm	D2 mm	-	Pk
RS-1	260850	1	-	-	54	-	5
D01100-0-086	260851	1	-	-	86	-	5
D01100-0-095	260852	1	-	-	95	-	5

