

# Verbindungssteile mit Vierkantantrieb nach DIN 3121 G



## Kugelgelenk – mit Federstift

Modell	Best.-Nr.	4kt Zoll	L mm	D1 mm	D2 mm	T mm	VE
KG1/4-45-FS	313350	1/4	40	18	13	–	–
KG3/8-55-FS	313351	3/8	60	25	22	–	–
KG1/2-75-FS	313353	1/2	74	31	25	–	–
KG1/2-100-FS	313354	1/2	100	30	25	–	–
KG1/2-150-FS	313355	1/2	150	30	25	–	–




## Kugelgelenk – mit Kugelsicherung

Modell	Best.-Nr.	4kt Zoll	L mm	D1 mm	D2 mm	T mm	VE
KG1/4-43-KS	313410	1/4	43	–	16	–	–
KG3/8-50-KS	313411	3/8	50	–	24	–	–
KG1/2-60-KS	313412	1/2	60	–	32	–	–
KG3/4-105-KS	313413	3/4	105	–	44	–	–



## Kugelgelenk – mit Stiftloch

Modell	Best.-Nr.	4kt Zoll	L mm	D1 mm	D2 mm	T mm	VE
KG1/4	313450	1/4	43	–	16	–	–
KG3/8	313451	3/8	50	–	24	–	–
KG1/2	313452	1/2	60	–	32	–	–
KG3/4	313453	3/4	90	–	44	–	–
KG3/4-L	313454	3/4	105	–	44	–	–
KG1	313455	1	133	–	54	–	–
KG1.1/2	313456	1 1/2	182	–	86	–	–



Weitere Infos  
rund um die  
Uhr auf unserer  
Website.

