

Kraftsteckschlüssel mit 1“ Vierkantantrieb nach DIN 3121 H 25



Halter & auswechselbare Einsätze

Modell	Best.-Nr.	SW mm	L mm	D1 mm	D2 mm	T mm	VE
K1-AWE22	260800	22	70	44,0	54	–	–
AWE22-A14	260810	14	50	–	–	–	–
AWE22-A17	260811	17	50	–	–	–	–
AWE22-A19	260812	19	50	–	–	–	–
AWE22-A22	260813	22	50	–	–	–	–
AWE22-A24	260814	24	50	–	–	–	–
AWE22-A27	260815	27	50	–	–	–	–
AWE22-A30	260816	30	50	–	–	–	–
AWE22-A32	260817	32	50	–	–	–	–
AWE22-A36	260818	36	50	–	–	–	–

Sechskant Inbus® – tief

Modell	Best.-Nr.	SW mm	L mm	D1 mm	D2 mm	L1 mm	VE
K1-A10-L	260710	10	100	–	54	20	–
K1-A12-L	260711	12	100	–	54	20	–
K1-A14-L	260712	14	100	–	54	20	–
K1-A17-L	260713	17	100	–	54	20	–
K1-A19-L	260714	19	100	–	54	20	–
K1-A22-L	260715	22	100	–	54	20	–
K1-A24-L	260717	24	100	–	54	20	–
K1-A27-L	260718	27	100	–	54	20	–
K1-A30-L	260719	30	100	–	54	24	–
K1-A32-L	260720	32	100	–	54	24	–
K1-A36-L	260722	36	100	–	54	28	–
K1-A22-EL	260716	22	140	–	54	20	–



Sechskant Inbus® – normal

Modell	Best.-Nr.	SW mm	L mm	D1 mm	D2 mm	L1 mm	VE
K1-A14	260649	14	75	–	54	12	–
K1-A17	260650	17	75	–	54	15	–
K1-A19	260651	19	75	–	54	17	–
K1-A22	260652	22	75	–	54	20	–
K1-A24	260653	24	75	–	54	20	–
K1-A27	260654	27	75	–	54	20	–
K1-A30	260655	30	75	–	54	20	–
K1-A32	260656	32	75	–	54	20	–
K1-A36	260657	36	75	–	54	20	–
K1-A41	260661	41	75	–	54	20	–
K1-A46	260666	46	75	–	54	20	–

Gummiring & Sicherungstift

Modell	Best.-Nr.	Größe Zoll	–	D1 mm	D2 mm	–	VE
RS-1	260850	1	–	–	54	–	5
D01100-0-086	260851	1	–	–	86	–	5
D01100-0-095	260852	1	–	–	95	–	5

