

Kraft-Steckschlüssel mit 1" Vierkantantrieb nach DIN 3121 H 25


NEU

NEU

Vierkant – normal

Modell	Best.-Nr.	SW #	L mm	D1 mm	D2 mm	L2 mm	VE
K1-17-VK	260001	17	57	52	52	24	–
K1-19-VK	260002	19	57	52	52	24	–
K1-20-VK	260003	20	57	52	52	24	–
K1-21-VK	260004	21	57	52	52	24	–

Sechskant – für Hochmomentschrauber

Modell	Best.-Nr.	SW mm	L mm	D1 mm	D2 mm	L2 mm	VE
KHT1-30	260200	30	85	51	54	21	–
KHT1-32	260202	32	85	53	54	22	–
KHT1-35	260203	35	85	57	54	22	–
KHT1-36	260204	36	85	58	54	25	–
KHT1-38	260206	38	85	61	54	25	–
KHT1-41	260207	41	85	64	54	27	–
KHT1-43	260209	43	85	68	54	27	–
KHT1-46	260210	46	85	72	54	30	–
KHT1-48	260212	48	85	74	54	32	–
KHT1-50	260214	50	85	77	58	35	–
KHT1-52	260216	52	85	79	58	35	–
KHT1-54	260218	54	85	82	58	35	–
KHT1-55	260219	55	85	83	58	35	–
KHT1-60	260220	60	85	89	58	42	–
KHT1-65	260221	65	85	95	58	42	–
KHT1-70	206222	70	85	102	58	42	–


NEU

Vierkant – normal – Zoll

Modell	Best.-Nr.	SW #	L mm	D1 mm	D2 mm	L2 mm	VE
K1-1-VK	260009	1"	60	52	54	30	–


NEU

Doppelvierkant – normal

Modell	Best.-Nr.	SW mm	L mm	D1 mm	D2 mm	L2 mm	VE
K1-19-DVK	260081	19	60	45	54	13	–
K1-24-DVK	260082	24	60	52	54	18	–
K1-27-DVK	260083	27	60	56,5	54	19	–
K1-30-DVK	260084	30	62	61	54	21	–
K1-32-DVK	260086	32	62	64	54	22	–
K1-35-DVK	260087	35	65	68,5	58	22	–
K1-38-DVK	260088	38	67	73	58	24	–
K1-46-DVK	260092	46	76	86	62	30	–



Gummiring / Sicherungsstift

Modell	Best.-Nr.	Größe Zoll	D1 mm	D2 mm	L1 mm	VE
DOESR-3	neu	1	5,4	44-67	36	5

